

Manufacturer (trade mark):	<b>Clover Germany</b>	Type/Model OEM:	<b>CLT-Y6092S/ELS</b>
Lot/Part number:	<b>0</b>	Toner color(s):	<b>YELLOW</b>
Main application:	To be used on the relevant printers according to remanufacturer instructions		
Intended yield:	<b>7000</b>	Take over value of existing test protocol :	
Test device:	<b>ZCZCBJZF200038V / ZCZCBJZCC00061Y</b>	(box) <b>Yes, from ISO19798</b>	
Test climate:			
Temperature:	<b>23</b>	Relative humidity: <b>44</b>	
Deviations of the determined test conditions			
Tester 1:	<b>Aleksandar Kojic</b>	Test location 2: <b>TRS EUROPE</b>	
Test date:	<b>30.11.2015</b>		

1) If values are taken over from test protocol, the signing person is responsible, that the protocols, from which the values have been taken off, are plausible and correct.

2) Either testing place or place where the protocol is made

Test sample (A)	Type	Used for valuation	Charge/Serial number
1 8328		Yes	Sample 1
2 7963		Yes	Sample 2
3 8145		Yes	We use for A1 the
4 7770		Yes	MAX, for A2 the
5 8005		Yes	MEDIAN and for A3 the
6 7963		Yes	MIN value of the list at
7 7703		Yes	left
8 7691		Yes	Sample 7
9 7854		Yes	Sample 8
			Sample 9
Comparing Sample (B)	Type	Used for valuation	Charge/Serial number
OEM data taken from OEMs own ISO19752 or ISO19798 declarations of yield	1 7000 2 7000 3 7000 4 5	Yes/no Yes/no Yes/no Yes/no Yes/no	OEM Sample/Spec OEM Sample/Spec OEM Sample/Spec  

#### Administrative checking of health related attributes (5.2)

Is there an EG- Safety Data Sheet of the used toner?

Yes/no **Yes**

If there are no information of the AMES test in the EG Safety Data Sheet

Yes/no **Not Applicable**

Is there a test report about the AMES test of the used toner?

If not: Description **All MSDSs mention Ames test**

#### Checking the influence of the toner module on the printer (5.3)

Is the toner leaking less than the original?

Yes/no **Yes**

Is the interaction between printer and toner module acceptable?

Yes/no **Yes**

If not: Description

#### Checking the initialization (5.4)

Is the print out acceptable right after the toner module has been inserted?

Yes/no **Yes**

If not: Describe fault

#### Checking the yield number (5.5)

**YELLOW**

**1**

**2**

**3**

**Average ( $\bar{A}$  or V)**

Yield A: $(A1+A2+A3)/3 = \bar{A}$	8328	7963	7691	7994
Yield V: $(V1+V2+V3)/3 = V$	7000	7000	7000	7000

**Alternative:**

Yield A: Result of test after ISO/IEC 19752  $\bar{A}$

Reference to the test protocol:

Test date:

Yield V: Result of test after ISO/IEC 19752 V

Reference to the test protocol:

Test date:

Result: EZ= $\bar{A}/V$

**1,14**

Yes

No

Not Applicable

**YES**

**YES**

#### Checking the black print/Color reproduction (5.6.2)

Average value of the 2 areas F test print A1: **86,4**

Average value of the 2 areas F comparing print V1: **86,5**

Difference is not higher than  $\Delta \leq 5$  for Monochrom

Color difference  $\Delta E \leq 18$  for Color **0,1**

Yes/No/Not Applicable **Not Applicable**

Yes/No/Not Applicable **Yes**

Average value of the 2 areas F test print A2: **85,8**

Average value of the 2 areas F comparing print V2: **86,5**

Difference is not higher than  $\Delta \leq 5$  for Monochrom

Color difference  $\Delta E \leq 18$  for Color **0,7**

Yes/No/Not Applicable **Not Applicable**

Yes/No/Not Applicable **Yes**

Average value of the 2 areas F test print A3: **84,7**

Average value of the 2 areas F comparing print V3: **86,4**

Difference is not higher than  $\Delta \leq 5$  for Monochrom

Not Applicable

Yes/No/Not Applicable **Not Applicable**

Yes/No/Not Applicable **Yes**

Color difference  $\Delta E \leq 18$  for Color 1,7Yes/No/Not Applicable Yes**Checking the fade (5.6.3)****YELLOW****Test print A1**

Color values 1 6 A F	1	6	A	F
after 50 pages	89,6	89,2	87,7	85,5
Color values 1 6 A F	1	6	A	F
The biggest deviation	2	1,5	1,5	1,7
<b>Comparing print V1</b>				
Color values 1 6 A F	1	6	A	F
after 50 pages	90,1	87,9	85,9	84
Color values 1 6 A F	1	6	A	F
The biggest deviation	3,7	3,1	3,5	3,9
<b>Result determination</b>	1	6	A	F
Difference $\Delta L \leq 8$	1,7	1,6	2	2,2
Difference within allowed parameters	YES	YES	YES	YES

**Test print A2 YELLOW**

Color values 1 6 A F	1	6	A	F
after 50 pages	91	88,8	86,7	84,4
Color values 1 6 A F	1	6	A	F
The biggest deviation	0,5	2	1,9	2,4
<b>Comparing print V2</b>				
Color values 1 6 A F	1	6	A	F
after 50 pages	89,7	88	86,4	84,3
Color values 1 6 A F	1	6	A	F
The biggest deviation	1,8	3,2	3,5	3,9
<b>Result determination</b>	1	6	A	F
Difference $\Delta L \leq 8$	1	1,2	1,6	1,5
Difference within allowed parameters	YES	YES	YES	YES

**Test print A3 YELLOW**

Color values 1 6 A F	1	6	A	F
after 50 pages	89,8	89,1	87,7	85,6
Color values 1 6 A F	1	6	A	F
The biggest deviation	0,8	0,5	1,1	1,4
<b>Comparing print V2</b>				
Color values 1 6 A F	1	6	A	F
after 50 pages	88,8	87,9	86,2	84,1
Color values 1 6 A F	1	6	A	F
The biggest deviation	2,7	3,5	3,7	4,1
<b>Result determination</b>	1	6	A	F
Difference $\Delta L \leq 8$	1,9	3	2,6	2,7
Difference within allowed parameters	YES	YES	YES	YES

**Checking toner adhesion**

Test process: visual (tape method):

Is the resistance in between the acceptable parameters?

Yes

If not: Describe deviation

**Checking the grey page/color uniformity (5.6.5)**Are the color differences in between the acceptable parameters (pattern B2-B5)  $\Delta E \leq 8$  ?

Yes

If not: Describe deviation

**Checking the background (5.6.6)**

Is the background smudge between the acceptable parameters (pattern B1-B5)?

Yes

If not: Describe deviation

**Checking the ghosting (5.6.7)**

Is the repeating of the back rectangles in between the acceptable parameters (pattern B2-B5)?

Yes

If not: Describe deviation

**Checking toner miscibility (5.6.8)**

Is the toner miscibility given?

N/A

If not: Describe deviation

**OVERALL RESULT: Passed**